SRH CLEAN REGULÁTOR SUS3016 - Z nerezové oceli s kontrolou kontaminace

Kód produktu: 74182

- Výrobce: SMC
- Materiál produktu: Nerez 316
- Médium: Čistý O2, N2, Argon, CO2, Voda...
- Pracovní teplota: 0°C až 60°C
- Norma výrobku: RoHs
- Použití produktu: Úprava tlaku vzduchu
- Zkrácená poznámka: Verze X210 má EPDM těsnění.

Clean regulátor série SRH je regulátor z nerezové oceli s kontrolovanou kontaminací navržený tak, aby minimalizoval zbytkovou kapalinu. Konstrukce zahrnuje sací/výfukový port v membránovém prostoru, který usnadňuje průtok. SRH má vynikající odolnost proti korozi. Všechny kovové části, které jsou v kontaktu s kapalinou, používají nerezovou ocel SUS316.



1 EPDM Seals — Symbol X210

Regulator with seals made of a different material.

SRH [Standard model no.] – X210 (EPDM seals)

Specifications

Model	SRH(L)-A24C	SRH(L)-A24	SRH(L)-A24	SRH(L)-A24
Relief mechanism	Non-relief		Relief	
Port size	Rc 1/8, 1/4 / URJR 1/4	Rc 1/4, 3/8, 1/2 / URJR 3/8	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2
Fluid (Grade A)	Dust air, N, O, Fire-extin		Clean air, N	
Fluid (Grade B)	Air, N, Ar, CO2, Water		Air, N	
Proof pressure	2.5 MPa			
Max. operating pressure	1.0 MPa			
Set pressure (Low pressure)	0.02 to 0.4 MPa			
Set pressure (High pressure)	0.05 to 0.7 MPa			
Ambient and fluid temperatures	0 to 60°C (No freezing)			
Valve/seat material (wet)	Stainless steel 316 (Body is stainless steel 316L)			
Diaphragm material (Grade A)	PTFE			
Diaphragm material (Grade B)	EPDM			
Weight	360 g	730 g	360 g	730 g



5 Aluminum Body — Symbol X234

The body material has been changed to aluminum.

SRH [Standard model no.] – X234 (Aluminum Body)

Specifications

Model	SRH(L)-A24C	SRH(L)-A24C	SRH(L)-A24	SRH(L)-A24
Relief mechanism	Non-relief		Relief	
Port size	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2	Rc 1/8, 1/4	Rc 1/4, 3/8, 1/2
Fluid (Grade B)	Air, N, Ar, CO2		Air, N	
Proof pressure	1.5 MPa			
Max. operating pressure	1.0 MPa			
Set pressure (Low pressure)	0.02 to 0.2 MPa			
Set pressure (High pressure)	0.05 to 0.7 MPa			
Ambient and fluid temperatures	0 to 60°C (No freezing)			
Valve/seat material (wet)	A2017 (Surface treatment: Anodized)			
Diaphragm material (Grade B)	Fluororubber			
Weight	230 g	360 g	230 g	360 g

Varianty zboží

Objednací kód	Hmotnost	Mj	Vaše cena bez DPH	Sklad
SMC-SRH3000-01-X210	0,337 kg	ks	28 173,00 Kč	
SMC-SRH3010-01-X210	0,34 kg	ks	28 173,00 Kč	